

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**

ABSTRACT OF THE DISCLOSURE

A pattern inspecting method, comprising preparing a sample having a first and a second inspection regions and an imaging device having a plurality of pixels, scanning the first inspection region to a first direction using the imaging device to obtain a first measurement pattern representing at least parts of the first inspection region, scanning the second inspection region to the first direction using the imaging device to obtain a second measurement pattern representing at least parts of the second inspection region, comparing the first measurement pattern and the second measurement pattern with each other to determine presence or absence of a defect formed on the sample, and controlling a scanning condition for scanning a pattern of the second inspection region by the imaging device so as to keep the same with the scanning condition when the pattern of the first inspection region is scanned by the imaging device.